


Type	: Alkaline High Drain Button Cell
Chemical System	: Alkaline Manganese Dioxide
Nominal Voltage	: 1.5Volts
Nominal Dimensions	: Ø11.6mm×5.4mm
Application	: Calculator, hearing aid, lighter, electronic, toy, camera, ... etc.
Average Weight	: 1.9g
Date Code	: Unless otherwise specified, each cell Will carry a numeric year code and an alphabetical month code.
Shelf Life	: Not less than 90% of the service capacity within first year. , not less than 85% of the service capacity with third year storage at 22 ± 3 °C 40-80%RH.
Close Circuit Voltage	: 1.30 Volts (min.)(load resistor 100Ω at 22 ± 3 °C for 0.1 to 2 seconds)
Nominal Service Life	: 255hrs (at 3.0 kΩ load) (to 1.0V at 22 ± 3 °C) 175 days (at 50 kΩ load)
Average Service Capacity	: 110mAh(at 6.2 kΩ load) (to 1.0V at 22 ± 3 °C)


Typical Discharge characteristics at 22 ± 3 °C



Cross References:

IEC JIS Eveready Varta Duracell

LR44 LR44 A76 V13GA LR44



* The information (subject to change without prior notice) contained in this document is for reference only and should not be used as a basis for product guarantee or warranty. For applications other than those described here, please consult your nearest GP Sales and Marketing Office or Distributors.